



## Wallbarn - Technical Datasheet

### Extension Shanks for Universal & Balance Pedestals



**20mm Ext Shank**

**SP-ASP-SHANK020-Z**



**30mm Ext Shank**

**SP-ASP-SHANK030-Z**

<b>EXTENSION SHANK MATERIAL</b>	Wallbarn Extension Shanks are manufactured from high quality polypropylene and are suitable for use with the Universal and Balance range of Pedestals. They are suited to normal atmospheric conditions with all technical, physical and mechanical properties maintained in the long-term. Manufacture of all Extension Shanks conform to quality management systems standard UNI EN ISO 9001:2008.
<b>APPLICATION</b>	The Extensions shanks are used as a contingency method for when the Finished Floor Level is uncertain. It makes for an easy fix for when some extra height is needed without having to pay for a full size pedestal.
<b>TECHNICAL DATA</b>	These polypropylene Shanks can be used with temperatures from -40°C to +75°C. The material is particularly resistant to sudden temperature changes, resists acid, alkaline, salts and atmospheric agents.

Wallbarn Ltd  
Unit 16 Capital Business Centre  
22 Carlton Road, South Croydon. CR2 0BS

IMS.T.1029.v1

Phone : 0208 916 2222 Email : [sales@wallbarn.com](mailto:sales@wallbarn.com) Website : [www.wallbarn.com](http://www.wallbarn.com)



# Wallbarn - Technical Datasheet

## 20mm & 30mm Extension Shanks

### Physical-Mechanical Properties

	Melt Flow Rate	Weight Density	VICAT with load of 5kg	HDT with load of 1,820 kPa	Coefficient of Elasticity	Impact Izod with engraving (IZOD at 23°C)	Impact IZOD with engraving (IZOD at -20°C)
TEST METHOD	ASTM D1238	ASTM D792 Method A	ASTM D1525	ASTM D648	ASTM D790	ASTM D256	ASTM D256
UNIT	Gr/10	Gr/cm <sup>3</sup>	°C	°C	Mpa	J/m	J/m
	14-16	0.99-1.04	>75	>90	>1600	>40	>20



Wallbarn Ltd  
 Unit 16 Capital Business Centre  
 22 Carlton Road, South Croydon. CR2 0BS

IMS.T.1029.v1