

Wallbarn - Technical Datasheet EPDM Corner Outlet - Smooth Flange



Product Description

The corner fittings have been designed to overcome the problem connecting the waterproof roofing felts with rain water drains placed close to walls. They have a smooth flange to improve bonding with adhesive of the EPDM roofing felt.

They have a square or rectangular section for systematic water drainage. The flange is slightly inclined to the shank to aid a slanted installation of the connector. The corner fitting can be installed in both horizontal and vertical drains.

Compatibility

They are compatible with EPDM prefabricated bituminous felts

Performance

Resistant to deterioration by the sun, ozone and normal atmospheric conditions. They have excellent flexibility even at low temperatures and will not become brittle. The mechanical properties are maintained in the long term.

Operating Temperatures Recycled Product

-20°C; +75°C No

Material Recyclable


EPDM-TPV Yes


Wallbarn Ltd
Unit 16 Capital Business Centre
22 Carlton Road, South Croydon. CR2 0BS

IMS.T.1075.v2



Wallbarn - Technical Datasheet





Product Code	Description	A	В	C	D	E	F
RO-EPDM-090-310- 065-100-Z	EPDM Corner Roof Outlet 90 Degree 65 x 100mm	65	100	427	150	155	280
RO-EPDM-090-310- 100-100-Z	EPDM Corner Roof Outlet 90 Degree 100 x 100mm	100	100	427	150	155	280